

Model iH



HIGH SPEED DIGITAL SUBLIMATION TEXTILE PRINTER

24 Hours Stable High Speed Production

16 Industrial Printing Heads for 4 Colors

Max Dally Output 15,000 Meters

625 ml/h

Focusing on textle industry for 32 years, Atexco will be with you forever.

Model iH Specifications

Model		Model iH
Printing Technology		Industrial DOD Piezo Printing
Print Heads Model/Quantity		Kyocera/16 pcs
Max. Printing Width		1820mm
Ink Supply System	Ink Type	Sublimation Ink
	Colors	4 Colors CMYK
	Ink Tank Volume	12L / color
Suitable Printing Media		Sublimation Paper
Printing Speed (Printing mode is chosen based on different designs)	Modes	Speed for Reference (1.5m wide)
	Mode 1 (300 1 Pass)	720 m/h
	Mode 2 (508 1 Pass)	480 m/h
	Mode 3 (300 2 Pass)	350 m/h
Max. Printing Media Width		1850mm
Paper Roll Feeder		Max 1100mm diameter/1200kg weight
Room Environment	Humidity	55%-70%
	Temperature	20°C-28°C
Computer System		WIN 10
Computer Configuration		Suggested I7-13700/32G/512G+SSD2T/64 bit
Display		User-machine Interface
Software	Server Software	AJet Server / Inedit NS
	Rip Software	Standard AJet RIP or third party software
Image Format		File Format JPEG/TIF/BMP ; Color Format RGB/CMYK
Language		Chinese/English
Power Supply		AC380V (3 Phase/5 Wires), 50HZ/60HZ
Power		24.5KW
Noise		60dB (It's up to the distance)
Machine Size/Weight		Around 4.10*2.65*1.90m / 2700Kg